

# Netgear 108 Mbps Wireless Router - \$20

Super fast! NETGEAR's WGT624NA 108 Mbps Wireless Firewall Router is 10 times faster than 802.11b routers. When used with NETGEAR's WG511T 108 Mbps Wireless PC Card, it delivers speeds up to 108 Mbps using Super G Technology. It has the power to distribute byte-hungry photos and smooth, long-range MP3 and digital movie streams at superior range.

Super secure! The WGT624 protects your network with over 10 security and privacy features including a double firewall (NAT + SPI), Multi-VPN (pass-through) support, and next generation wireless encryption WPA (pre-shared key).

Super easy! NETGEAR's Smart Wizard gets you connected in 5 clicks or less!



<i>Extended Specifications</i>	
<b>General</b>	
<b>Device Type</b>	Wireless router
<b>Form Factor</b>	External
<b>Built-in Devices</b>	Antenna
<b>Approximate Width</b>	6.9 in
<b>Approximate Depth</b>	7.4 in
<b>Approximate Height</b>	1.1 in
<b>Approximate Weight</b>	0.7 lbs
<b>Networking</b>	
<b>Connectivity Technology</b>	Wireless, wired
<b>Integrated Switch</b>	4-port switch

<b>Data Transfer Rate</b>	108 Mbps
<b>Frequency Band</b>	2.4 GHz
<b>Line Coding Format</b>	DBPSK, DQPSK, CCK, 64 QAM, BPSK, QPSK, 16 QAM, OFDM
<b>Data Link Protocol</b>	Ethernet, Fast Ethernet, IEEE 802.11b, IEEE 802.11g
<b>Network / Transport Protocol</b>	TCP/IP, PPTP, L2TP, IPSec, PPPoE
<b>Routing Protocol</b>	Static IP routing
<b>Status Indicators</b>	Link activity, port transmission speed, power, test mode
<b>Features</b>	Firewall protection, DMZ port, auto-sensing per device, DHCP support, NAT support, Stateful Packet Inspection (SPI), DoS attack prevention, content filtering, manageable, E-mail alert, VPN passthrough
<b>Compliant Standards</b>	IEEE 802.11b, IEEE 802.11g
<b>Expansion / Connectivity</b>	
<b>Interfaces</b>	1 x network - Radio-Ethernet 4 x network node - Ethernet 10Base-T/100Base-TX - RJ-45 1 x network - Ethernet 10Base-T/100Base-TX - RJ-45 ( WAN )
<b>Miscellaneous</b>	
<b>Cables (Details)</b>	1 x network cable
<b>Encryption Algorithm</b>	128-bit WEP, 152-bit WEP, 40-bit WEP, WPA
<b>Authentication Method</b>	Radio Service Set ID (SSID)
<b>Compliant Standards</b>	FCC Class B certified, CE
<b>Power</b>	
<b>Power Device</b>	Power adapter - external
<b>Software / System Requirements</b>	
<b>Software Included</b>	Drivers & Utilities

<b>OS Required</b>	Microsoft Windows 98, UNIX, Apple MacOS, Novell NetWare, Linux, Microsoft Windows NT, Microsoft Windows Millennium Edition, Microsoft Windows 2000 / XP
<b>Manufacturer Warranty</b>	
<b>Service &amp; Support</b>	1 year warranty
<b>Service &amp; Support Details</b>	Limited warranty - 1 year
<b>Environmental Parameters</b>	
<b>Min Operating Temperature</b>	32 °F
<b>Max Operating Temperature</b>	104 °F
<b>Humidity Range Operating</b>	0 - 90%